Minimum Specifications For 2D Barcode Reader

| | Required Minimum Specification | | Response |
|----|---|--|----------|
| 1 | Brand | Specify (Should be internationally) | |
| 2 | Model | specify | |
| 3 | Country of Origin | Specify | |
| 4 | Year of Manufacture | Specify | |
| 5 | Input Voltage Range | 4.0 to 5.0 VDC host powered | |
| 6 | Operating Current at Nominal Voltage – Presentation Mode | 330mA or above | |
| 7 | Speed (Presentation) | Up to 120 in. | |
| 8 | Light Source | LED | |
| 9 | Image Sensor | 1280 x 800 pixels | |
| 10 | Scan Mode | Auto scan and search mode should be available | |
| 11 | Contrast | 15% or above | |
| 12 | Skew / Pitch Tolerance | +/- 600 | |
| 13 | Graphics Format Support | Bitmap, JPEG, TIFF | |
| 14 | Supported Host Interface | USB, RS232, Please Specify | |
| 15 | Indicators | LEDs & Beeper | |
| 16 | Dimension | Please specify (HxWxD) | |
| 17 | Weight | Please Specify | |
| 18 | Warranty | 01 Year Warranty | |
| 19 | Manufacture Authorization Certificates | Attached with Bidder's rubber stamp and signature e-mail loop should send to | |
| 20 | Product brochure URL | Please Send e-mail to | |
| 21 | Bidders Experience & Qualification | 8 Years' Experience with after-sales service with the 5 Years for product BRAND . | |

| Bidder's Signature |
|--------------------|